



Cummins Inc.
Columbus, Indiana 47202-3005
Engine Data Sheet

Basic Engine Model:
QSB5-G2 NR3

Curve Number:
FR-92203

G-DRIVE
QSB
1

Engine Critical Parts List:
CPL:1100

Date:
17Sep07

Displacement : **4.5 litre (275 in³)**

Bore : **107 mm (4.21 in.)** Stroke : **124 mm (4.88 in.)**


No. of Cylinders : **4**

Aspiration : **Turbocharged and Air to Air Aftercooled**

| Engine Speed rpm | Standby Power | | Prime Power | | Continuous Power | |
|---------------------|---------------|-----|-------------|-----|------------------|-----|
| | kWm | hp | kWm | hp | kWm | hp |
| 1500 | 84 | 113 | 73 | 98 | 66 | 89 |
| 1800 | 96 | 129 | 84 | 112 | 77 | 103 |


Engine Performance Data @ 1500 rpm

| OUTPUT POWER | | | FUEL CONSUMPTION | | | |
|-------------------------|-----|-----|------------------|-------------|----------------|-----------------|
| % | kWm | hp | kg/ kWm·h | lb/ hp·h | litre/ hour | US gal/ hour |
| STANDBY POWER | | | | | | |
| 100 | 84 | 113 | 0.227 | 0.373 | 22 | 5.9 |
| PRIME POWER | | | | | | |
| 100 | 73 | 98 | 0.237 | 0.390 | 20 | 5.4 |
| 75 | 55 | 74 | 0.243 | 0.400 | 16 | 4.1 |
| 50 | 37 | 49 | 0.244 | 0.402 | 11 | 2.8 |
| 25 | 18 | 25 | 0.265 | 0.436 | 6 | 1.5 |
| CONTINUOUS POWER | | | | | | |
| 100 | 66 | 89 | 0.241 | 0.397 | 19 | 5.0 |



Engine Performance Data @ 1800 rpm

| OUTPUT POWER | | | FUEL CONSUMPTION | | | |
|-------------------------|-----|-----|------------------|-------------|----------------|-----------------|
| % | kWm | hp | kg/ kWm·h | lb/ hp·h | litre/ hour | US gal/ hour |
| STANDBY POWER | | | | | | |
| 100 | 96 | 129 | 0.229 | 0.376 | 26 | 6.8 |
| PRIME POWER | | | | | | |
| 100 | 84 | 112 | 0.232 | 0.382 | 23 | 6.0 |
| 75 | 63 | 84 | 0.256 | 0.421 | 19 | 5.0 |
| 50 | 42 | 56 | 0.260 | 0.427 | 13 | 3.4 |
| 25 | 21 | 28 | 0.306 | 0.502 | 8 | 2.0 |
| CONTINUOUS POWER | | | | | | |
| 100 | 77 | 103 | 0.240 | 0.395 | 22 | 5.7 |



CONVERSIONS:(litres = US Gal x 3.785) (US Gal = litres x 0.2642)

Data Subject to Change Without Notice

These guidelines have been formulated to ensure proper application of generator drive engines in A.C. generator set installations. **STANDBY POWER RATING:** Applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the Standby Power rating. This rating should be applied where reliable utility power is available. A Standby rated engine should be sized for a maximum of an 80% average load factor and 200 hours of operation per year. This includes less than 25 hours per year at the Standby Power rating. Standby ratings should never be applied except in true emergency power outages. Negotiated power outages contracted with a utility company are not considered an emergency. **PRIME POWER RATING:** Applicable for supplying electric power in lieu of commercially purchased power. Prime Power applications must be in the form of one of the following two categories: **UNLIMITED TIME RUNNING PRIME POWER:** Prime Power is available for an unlimited number of hours per year in a variable load application. Variable load should not exceed a 70% average of the Prime Power rating during any operating period of 250 hours. The total operating time at 100% Prime Power shall not exceed 500 hours per year. A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year. **LIMITED TIME RUNNING PRIME POWER:** Limited Time Prime Power is available for a limited number of hours in a non-variable load application. It is intended for use in situations where power outages are contracted, such as in utility power curtailment. Engines may be operated in parallel to the public utility up to 750 hours per year at power levels never to exceed the Prime Power rating. The customer should be aware, however, that the life of any engine will be reduced by this constant high load operation. Any operation exceeding 750 hours per year at the Prime Power rating should use the Continuous Power rating. **CONTINUOUS POWER RATING:** Applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.

Reference AEB 10.47 for determining Electrical Output.

Data shown above represent gross engine performance capabilities obtained and corrected in accordance with ISO-3046 conditions of 100 kPa (29.53 in Hg) barometric pressure [110 m (361 ft) altitude], 25 °C (77 °F) air inlet temperature, and relative humidity of 30% with No. 2 diesel or a fuel corresponding to ASTM D2. Derates shown are based on 10 in H₂O air intake restriction and 2 in Hg exhaust back pressure.

The fuel consumption data is based on No. 2 diesel fuel weight at 0.85 kg/litre (7.1 lbs/US gal). Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan, optional equipment and driven components.





Data Status: --Preliminary--

Data Tolerance: ± 5%

Chief Engineer:

1500 rpm Derate Curves

1800 rpm Derate Curves



Operation At Elevated Temperature And Altitude:

For **Standby/Prime operation** above these conditions, derate by an additional 5.0% per 300 m (1000 ft), and 14% per 10° C (18° F).
 For **Continuous operation** above these conditions, derate by an additional 6.0% per 300 m (1000 ft), and 16% per 10° C (18° F).

Operation At Elevated Temperature And Altitude:

For **Standby/Prime operation** above these conditions, derate by an additional 7.0% per 300 m (1000 ft), and 21% per 10° C (18° F).
 For **Continuous operation** above these conditions, derate by an additional 8% per 300 m (1000 ft), and 25% per 10° C (18° F).

Cummins Inc.
Engine Data Sheet

ENGINE MODEL : QSB5-G2 NR3 **CONFIGURATION NUMBER : D323007GX03**

DATA SHEET : DS-92203

DATE : 17Sep07

PERFORMANCE CURVE : FR-92203

INSTALLATION DIAGRAM

• Fan to Flywheel: 4953685

CPL NUMBER

• Engine Critical Parts List: 1100

GENERAL ENGINE DATA

| | |
|---|-------------------------------------|
| Type | 4-Cycle; In-line; 4-Cylinder Diesel |
| Aspiration | Turbocharged and Charge Air Cooled |
| Bore x Stroke | 4.21 x 4.88 (107 x 124) |
| Displacement | 275 (4.5) |
| Compression Ratio | 17.3 : 1 |
| Dry Weight (Approximate), Fan to Flywheel Engine | 776 (352) |
| Wet Weight (Approximate), Fan to Flywheel Engine | 818 (371) |
| Moment of Inertia of Rotating Components | |
| • with FW 9857 Flywheel | 16.9 (0.71) |
| • with FW 9878 Flywheel | 29.0 (1.22) |
| Center of Gravity from Rear Face of Block | 9.4 (239) |
| Center of Gravity Above Crankshaft Centerline | 6.4 (163) |
| Maximum Static Loading at Rear Main Bearing | N.A. (N.A.) |

ENGINE MOUNTING

| | |
|--|-------------|
| Maximum Bending Moment at Rear Face of Block | 1000 (1356) |
|--|-------------|

EXHAUST SYSTEM

| | |
|-----------------------------|--------|
| Maximum Back Pressure | 3 (10) |
|-----------------------------|--------|

AIR INDUCTION SYSTEM

| | |
|-----------------------------------|----------|
| Maximum Intake Air Restriction | |
| • with Dirty Filter Element | 25 (6.2) |
| • with Clean Filter Element | 15 (3.7) |

COOLING SYSTEM

Jacket Water Circuit Requirements

| | |
|--|-------------------|
| Coolant Capacity — Engine Only | 2.25 (8.5) |
| Maximum Static Head of Coolant Above Engine Crank Centerline | 60 (18.3) |
| Standard Thermostat (Modulating) Range | 175-203 (79-95) |
| Minimum Pressure Cap | 15 (103) |
| Maximum Top Tank Temperature for Standby / Prime Power | 233/225 (112/107) |
| Maximum Coolant Friction Head External to Engine | 5 (35) |

Charge Air Cooler Requirements

| | |
|--|------------------|
| Maximum Temp. Rise Between Engine Air Intake and Intake Manifold - 1500/1800 rpm | 45 (25) |
| Maximum Air Pressure Drop from Turbo Air outlet to Intake Manifold - 1500/1800 rpm | 2.5/4 (8.5/13.5) |
| Maximum Intake Manifold Temperature @ 77 °F (25 °C) ambient - 1500/1800 rpm | 122 (50) |
| Maximum Intake Manifold Temperature for engine protection (Shut Down Threshold) | 210 (99) |

LUBRICATION SYSTEM

| | |
|---|-----------------|
| Oil Pressure @ Idle Speed | 10 (69) |
| @ Governed Speed | 40-60 (276-414) |
| Maximum Oil Temperature | 280 (138) |
| Oil Capacity with OP 9458 Oil Pan : Low -High | 2.4-2.9 (9-11) |
| Total System Capacity (Including Filter) | 3.2 (12.2) |

FUEL SYSTEM

| | | |
|--|--------------|-------|
| Type Injection System | Bosch HPCR | |
| Maximum Restriction at Lift Pump (clean/dirty filter) | 5/10 (17/34) | |
| Maximum Allowable Head on Injector Return Line (Consisting of Friction Head and Static Head) | 6 | (20) |
| Maximum Fuel Flow to Injector Pump. | 35 | (133) |
| Maximum Return Fuel Flow. | 33 | (125) |
| Maximum Fuel Inlet Temperature | 160 | (71) |

ELECTRICAL SYSTEM

| | | |
|--|-------|-------|
| Cranking Motor (Heavy Duty, Positive Engagement) | 12 | 24 |
| Battery Charging System, Negative Ground | 100 | 70 |
| Maximum Allowable Resistance of Cranking Circuit | 0.001 | 0.002 |
| Minimum Recommended Battery Capacity | | |
| • Cold Soak @ 0 °F to 32 °F (-18 °C to 0 °C) | 1000 | (500) |

COLD START CAPABILITY

| | | |
|---|----|-------|
| Minimum Ambient Temperature for NFPA 110 Cold Start (90 degree F Coolant Temperature) | 10 | (-12) |
| Minimum Ambient Temperature for Unaided Cold Start | 10 | (-12) |

PERFORMANCE DATA

- All data is based on:
- Engine operating with fuel system, water pump, lubricating oil pump, air cleaner and exhaust silencer; not included are battery charging alternator, fan, and optional driven components.
 - Engine operating with fuel corresponding to grade No. 2-D per ASTM D975.
 - ISO 3046, Part 1, Standard Reference Conditions of:

| | |
|---|---------------------------------|
| Barometric Pressure : 100 kPa (29.53 in Hg) | Air Temperature : 25 °C (77 °F) |
| Altitude : 110 m (361 ft) | Relative Humidity : 30% |

| | | |
|--|-----|---------|
| Steady State Stability Band at Any Constant Load | % | +/-0.25 |
| Excludes Exhaust Noise; at Rated Load and 7.5 m (24.6 ft); @1800 rpm | dBA | 88 |
| Exhaust Noise at 1 m Horizontal from Centerline of Exhaust Pipe Outlet Upwards at 45 ° | dBA | 109 |

| | |
|---|------------------|
| Governed Engine Speed | rpm |
| Engine Idle Speed | rpm |
| Gross Engine Power Output | hp (kW) |
| Brake Mean Effective Pressure | psi (kPa) |
| Piston Speed | ft/min (m/s) |
| Friction Horsepower | hp (kW) |
| Engine Water Flow at Stated Friction Head External to Engine: | |
| • 2.5 psi Friction Head | US gpm (litre/s) |
| • Maximum Friction Head | US gpm (litre/s) |

| | STANDBY POWER | | PRIME POWER | |
|---|---------------|------------|-------------|------------|
| | 60 hz | 50 hz | 60 hz | 50 hz |
| | 1800 | 1500 | 1800 | 1500 |
| | 700 - 900 | 700 - 900 | 700 - 900 | 700 - 900 |
| Gross Engine Power Output | 129 (96) | 113 (84) | 112 (84) | 98 (73) |
| Brake Mean Effective Pressure | 207 (1427) | 217 (1496) | 181 (1248) | 191 (1317) |
| Piston Speed | 1464 (7.4) | 1220 (6.2) | 1464 (7.4) | 1220 (6.2) |
| Friction Horsepower | 17 (13) | 12 (9) | 17 (13) | 12 (9) |
| Engine Water Flow at Stated Friction Head External to Engine: | | | | |
| • 2.5 psi Friction Head | 43 (1.8) | 34 (2.2) | 43 (2.8) | 34 (2.2) |
| • Maximum Friction Head | 39 (2.5) | 30 (1.9) | 39 (2.5) | 30 (1.9) |
| Intake Air Flow | 320 (150) | 245 (120) | 305 (145) | 245 (115) |
| Exhaust Gas Temperature | 840 (450) | 910 (490) | 795 (425) | 885 (475) |
| Exhaust Gas Flow | 735 (350) | 620 (295) | 730 (345) | 600 (285) |
| Air to Fuel Ratio | 28.5 : 1 | 25.6 : 1 | 30.7 : 1 | 27.4 : 1 |
| Radiated Heat to Ambient | 587 (10) | 512 (9) | 526 (9) | 472 (8) |
| Heat Rejection to Jacket Coolant | 2488 (44) | 2233 (39) | 2237 (39) | 2110 (37) |
| Heat Rejection to Exhaust | 4658 (82) | 4034 (71) | 4170 (73) | 3830 (67) |
| Heat Rejected to Fuel* | 65 (1) | 45 (1) | 65 (1) | 43 (1) |
| Heat Rejected to Aftercooler | 1326 (23) | 971 (17) | 1202 (21) | 917 (16) |
| Charge Air Flow | 23 (10) | 18 (8) | 22 (10) | 18 (8) |
| Turbocharger Compressor Outlet Pressure | 26 (180) | 22 (152) | 24 (166) | 21 (146) |
| Turbocharger Compressor Outlet Temperature | 353 (178) | 326 (163) | 337 (169) | 317 (158) |

Engine Data with Dry Type Exhaust Manifold

| | |
|--|-----------------|
| Intake Air Flow | cfm (litre/s) |
| Exhaust Gas Temperature | °F (°C) |
| Exhaust Gas Flow | cfm (litre/s) |
| Air to Fuel Ratio | air : fuel |
| Radiated Heat to Ambient | BTU/min (kW) |
| Heat Rejection to Jacket Coolant | BTU/min (kW) |
| Heat Rejection to Exhaust | BTU/min (kW) |
| Heat Rejected to Fuel* | BTU/min (kW) |
| Heat Rejected to Aftercooler | BTU/min (kW) |
| Charge Air Flow | lb/min (kg/min) |
| Turbocharger Compressor Outlet Pressure | psi (kPa) |
| Turbocharger Compressor Outlet Temperature | °F (°C) |

* This is the maximum heat rejection to fuel.

N.A. - Not Available
N/A - Not Applicable to this Engine
TBD - To Be Determined

ENGINE MODEL : QSB5-G2 NR3
DATA SHEET : DS-92203
DATE : 17Sep07
CURVE NO. : FR-92203