

Baldor Diesel Industrial Generators

Portable Diesel Model ^①	DG3E	DG6E
Features		
Switchless Full Pow'r	inc	inc
AC Voltmeter	inc	inc
Hourmeter	inc	inc
Low Oil Shutdown	inc	inc
Spark Arrestor Muffler	inc	inc
Extended Run Fuel Tank	inc	inc
Tubular Roll Cage	inc	inc
Neoprene Isolators	inc	inc
Focal Vibration System (FVS)	inc	inc
3-Year Warranty ^②	inc	inc
Engine Model		
	Hatz 1B30	Hatz 1B40
Horsepower	5.5	9.9
Cylinder (S)	1	1
Displacement - CC	346	461.9
Starting Systems ^③	12 Volt with Recoil	12 Volt with Recoil
Rating		
Max Rating	3300	6000
Rated	3000	5500
Volts	120/240 VAC	120/240 VAC
Amps	25/12.5	45.8/22.9
Receptacles		
Straight (520R) 120V		
Straight (515R GFCI) 120V	2-20 AMP	4-20 AMP
Straight (520R GFCI) 120V		
Twist Lock (L530R) 120V	1-30 AMP	1-30 AMP
Twist Lock (L1430R) 120V/240		1-30 AMP
Twist Lock (L1420R) 120V		
Twist Lock (L1420R) 120/240V	1-20 AMP	
Other		
Fuel Capacity (U.S. Gallons)	2.75	4.6
Operational Run Time on 1 tankful	9 hr	4.6-6 hr
Dimensions		
Length	24.5"	32"
Width	18.5"	20.5"
Height	21.75"	23.75"
Weight	172 lbs	246 lbs



DG6E

BALDOR
GENERATORS